40 CFR Ch. I (7-1-00 Edition)

Subpart B

Direct Chill Casting Contact Cooling

Water

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cast	
Chromium	0.59 0.39	0.24 0.16
Zinc	1.94 8.55	0.81 4.26

SUBPART B

Solution Heat Treatment Contact Cooling Water

	BAT Effluent Limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum quenched	
Chromium	0.90	0.37
Cyanide	0.59	0.25
Zinc	2.98	1.25
Aluminum	13.10	6.52

Subpart B

Cleaning or Etching Bath

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium	0.079 0.052 0.26 1.15	0.032 0.022 0.109 0.573

SUBPART B

Cleaning or Etching Rinse

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium Cyanide Zinc Aluminum	0.61 0.41 2.03 8.95	0.25 0.17 0.85 4.45

SUBPART B

Cleaning or Etching Scrubber Liquor

	BAT effluent limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium	0.85 0.56 2.82 12.43	0.35 0.23 1.18 6.19

[48 FR 49149, Oct. 24, 1983; 49 FR 11631 and 11633, Mar. 27, 1984]

Any new source subject to this subpart must achieve the following performance standards. The discharge of process wastewater pollutants from the core shall not exceed the values set forth below:

Subpart B

Core

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum rolled with emul sions	
Chromium	0.048	0.020
Cyanide	0.026	0.011
Zinc	0.133	0.055
Aluminum	0.80	0.35
Oil and grease	1.30	1.30
Suspended solids	1.95	1.56
pH	(1)	(1)

¹ Within the range of 7.0 to 10.0 at all times.

Environmental Protection Agency

Subpart B

Direct Chill Casting Contact Cooling Water

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/m aluminum semicontinuo	
Chromium	0.49	0.20
Cyanide	0.27	0.11
Zinc	1.36	0.56
Aluminum	8.12	3.60
Oil and grease	13.29	13.29
Suspended solids	19.94	15.95
pH	(1)	(1)

¹The pH shall be maintained within the range of 7.0 to 10.0 at all times except for those situations when this waste stream is discharged separately and without commingling with any other wastewater in which case the pH shall be within the range of 6.0 to 10.0 at all times.

Subpart B

Solution Heat Treatment Contact Cooling Water

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum quenched	
Chromium	0.76	0.31
Cyanide	0.41	0.17
Zinc	2.08	0.86
Aluminum	12.45	5.52
Oil and grease	20.37	20.37
Suspended solids	30.56	24.45
pH	(1)	(1)

 $^{^{\}mbox{\scriptsize 1}}\mbox{Within the range of 7.0 to 10.0 at all times.}$

SUBPART B Cleaning or Etching Bath

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) aluminum cleaned or etche	
Chromium	0.067 0.036	0.027 0.015
Zinc	0.183	0.075
Aluminum	1.094 1.79	0.485 1.79
Suspended solids	2.69	2.15
nH	(1)	(1)

 $^{^{\}mbox{\tiny l}}$ Within the range of 7.0 to 10.0 at all times.

SUBPART B

Cleaning or Etching Rinse

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		nillion off-lbs) of aned or etched
Chromium	0.52	0.21
Cyanide	0.28	0.11
Zinc	1.42	0.59
Aluminum	8.50	3.77
Oil and grease	13.91	13.91
Suspended solids	20.87	16.70
pH	(1)	(1)

¹ Within the range of 7.0 to 10.0 at all times.

SUBPART B

Cleaning or Etching Scrubber Liquor

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		nillion off-lbs) of aned or etched
Chromium	0.72	0.29
Cyanide	0.39	0.16
Zinc	1.97	0.81
Aluminum	11.81	5.24
Oil and grease	19.33	19.33
Suspended solids	29.00	23.20
pH	(1)	(1)

¹ Within the range of 7.0 to 10.0 at all times.

[48 FR 49149, Oct. 24, 1983; 49 FR 11631 and 11633, Mar. 27, 1984, as amended at 53 FR 52370, Dec. 27, 1988]

§ 467.25 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources. The mass of wastewater pollutants in aluminum forming process wastewater introduced into a POTW shall not exceed the following values: